Chemcoat, Inc. "Consistent Coatings...Superior Service"

PO Box 188, Montoursville PA 17754 800-326-9471

SAFETY DATA SHEET

Section 1 - Chemical Product and Company Information

Product Name: W/B High Definition Sealer Product Code: 96R-221

Manufactured by: IN CASE OF EMERGENCY:

Chemcoat Inc. P.O. Box 188 2790 Canfield Lane Montoursville. PA 17754

Chem-tel 800-255-3924

~ .:	\sim	1.1		1 1	1:6:	. (!
Section	·) _	Haza	ırde	Ider	ハナリナリヘク	ation
OCCHOIL		1 102.0	แนง	IUCI		นแบบ

GHS Ratings:

GHS Hazards

GHS Precautions

Signal Word:

Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %	
Chlorobenzotrifluoride	98-56-6	10.24%	

Section 4 - First Aid Measures

INHALATION - Move person to fresh air. If breathing has stopped, administer artifical respiration. Seek medical

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water.

SDS for: 96R-221 Page 1 of 4

INGESTION - Do not induce vomiting. This may cause chemical pneumonitis and pulmonary edema. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point: > 100 C (>212 F)

LEL:

UEL:

Extinguishing Media: Use carbon dioxide (CO2), foam, dry chemical, or water spray/water fog extinguishing system.

Unusual Fire and Explosion Hazards: Vapors may travel considerable distance by air and become ignited by ignition sources.

Hazardous Combustion Products: Oxides of carbon

Fire Fighting Instructions: Full protective equipment including self contained breathing apparartus should be used.

Fire Equipment: Water spray may not be effective, use fog nozzles

Section 6 - Accidental Release Measures

Spill and Leak Procedure: Eliminate all ignition sources. Ventilate the area. Use appropriate respirator and protective clothing.

Small Spills: Contain spill areas with dikes. Recover spilled material into containers. Absorb remainder with absorbent material.

Large Spills: If small spill measures do not contain the spill, notify local authorities and/or the fire department.

Section 7 - Handling and Storage

Handling: Avoid prolonged breathing or contact with product. Keep containers closed when not in use. Do not cut, drill, grind, or weld near containers even when empty. Use non-sparking tools when working around this material. Storage Requirements: Protect from freezing. Keep containers closed when not in use. Keep away from excessive heat, open flames, or sparks.

Regulatory Requirments: Consult national, state and local environmental laws.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Chlorobenzotrifluoride 98-56-6	Not Established	Not Established	CEL: 25 ppm 8 hr TWA

Ventilation: Exhaust as required to keep exposure below Threshold Limit Values

Protective Gear: If ventilation equipment cannot control exposures below the TLV's, wear a properly fitted organic/particulate NIOSH/MSHA approved respirator. Wear rubber or neoprene protective gloves for repeated or prolonged skin contact. Wear safety glasses or face shield for eye protection.

Section 9 - Physical and Chemical Properties

Appearance Viscous liquid dispersion	Physical State Liquid	
Vapor Density Heavier then air	Vapor Pressure 4.5 mbar @ 20 C	
Evaporation Rate Faster than ether	Boiling Range 100 to 139 °C	
Specific Gravity (SG) 1.010	Formula Lb / Gal 8.41	

SDS for: 96R-221

Lbs VOC/Gallon Solids 0.41 % Volume Volatile (VOC) 73.16 Ibs/gal VOC as supplied (), 11 % Organic Sovent 11.55

Section 10 - Stability and Reactivity

Stability:

STABLE

Incompatibility: Strong acids or bases.

Strong oxidizing agents

Hazardous Decomposition: Oxides of carbon and nitrogen.

Chlorine containing gases can be produced

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 21mg/L

Component Toxicity

98-56-6

Chlorobenzotrifluoride

Dermal LD50: 3,300 mg/kg (rabbit) Inhalation LC50: 33 mg/L (rat)

Routes of Entry:

Inhalation

Skin Contact

Eve Contact

Ingestion

Exposure to this material may affect the following organs:

Eyes

Skin

Effects of Overexposure

Short Term

Causes local irritation to skin, eyes and mucous membranes. May cause

Exposure

irritation by any route of exposure. The LD50 rat is 13 gm/kg (13,000 mg/kg)

(insignificantly toxic).

Long Term

There is evidence that this chemical is a mutagen.

Exposure

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA, or ACGIH.

CAS Number

Description

% Weight

Carcinogen Rating

None

None

Section 12 - Ecological Information

Ecotoxicity: Protect environment from spills and releases.

Component Ecotoxicity

Section 13 - Disposal Considerations

Disposal: As the US EPA, state, local or other regulatory agency may have jurisdiction over the disposal of your facility's waste, it is incumbent on you, to learn and satisfy all the regulations which effect you. Dispose of in accordance to government regulations. Destroy by liquid incineration by certified environmental service group.

Section 14 - Transport Information

Protect from freezing.

SDS for: 96R-221 Page 3 of 4 Agency DOT

Proper Shipping Name

Paint

*- Not required

**- Not regulated

Not req*

UN Number Packing Group Hazard Class

Not reg**

Section 15 - Regulatory Information

Additional regulatory lisitings where applicable

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations, part 372.

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HEALTH FLAMMABILITY PHYSICAL HAZARD PERSONAL PROTECTION

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



Every effort has been made to ensure that the safety information on this sheet is accurate, but because Chemcoat, Inc. has no control over the condition under which the product will be used, liability is limited exclusively to replacement or refund of the purchased price of this product. Except as stated herein, there are NO EXPRESS OR IMPLIED WARRANTIES INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FINESS FOR A PARTICULAR PURPOSE. Chemcoat, Inc. assumes no liability for injury or incidental or consequential damages arising out of the storage and handling or use of this product.

Reviewer Revision

Date Prepared: 2/20/2018

SDS for: 96R-221

Page 4 of 4

Printed: 2/20/2018 at 11:49:43AM